

G-TAS

柴油引擎發電機組 GENERATING SET

DEUTZ SERIES			RATINGS (kw) / 額定輸出 (仟瓦)		APPROXIMATE DIMENSIONS 開放型約略尺寸				
S/no 序號	genset model 發電機組型號	engine model 引擎型號	Emissions Level	60hz/1800rpm prime	standby	L/長 mm	W/寬 mm	H/高 mm	weight/重量 kg
1	GDD-30	BF4M2011	Tier 3	27	30	1700	760	1200	750
2	GDD-40	BF4M2011	Stage-2	36	40	1850	760	1300	850
3	GDD-60	BF4M2012	Stage-2	54	60	2000	760	1500	950
4	GDD-80	BF4M1013EC G2	Stage-2	72	80	2150	810	1890	1300
5	GDD-100	BF4M1013FC	Stage-2	90	100	2400	810	1700	1350
6	GDD-125	BF6M1013EC	Stage-2	113	125	2700	850	1800	1450
7	GDD-150	BF6M1013FC G2	Stage-2	135	150	2700	850	1800	1500
8	GDD-175	BF6M1013FC G2	Stage-2	158	175	2600	1000	1550	1700
9	GDD-200	BF6M1013FC G3	Stage-2	180	200	2900	1000	1550	2200
10	GDD-250	BF6M1015C	Stage-2	225	250	3000	1150	1700	2300
11	GDD-300	BF6M1015C	Stage-2	270	300	3300	1150	1700	2800
12	GDD-350	BF8M1015C	Stage-2	315	350	3300	1150	1700	2800
13	GDD-400	BF8M1015C	Stage-2	360	400	3400	1150	1950	2950
14	GDD-450	BF8M1015CP	Stage-2	405	450	3700	1150	1750	2950

prime power : Overload of 10% is permitted for one hour in twelve hours operation.

連續輸出：每12小時運轉中，具有超載 10% 1個小時的能力。

standby power : no overload is permitted.

緊急輸出：無超載能力之最大輸出容量。

