



DIESEL ENGINES GENERATOR SET

CUMMINS SERIES			RATINGS(kWe)				APPROXIMATE DIMENSIONS			
S/no	genset model	engine model	50hz/1500rpm		60hz/1800rpm		L mm	W mm	H mm	weight kg
			prime	standby	prime	standby				
1	GCD-150	QSB7-G3	120	140	136	150	2700	1100	1550	1260
2	GCD-200	6CTAA8.3-G1	160	180	180	200	3000	1100	1500	1650
3	GCD-250	QSL9-G3	200	220	225	250	3000	1100	1800	2500
4	GCD-300	QSL9-G7	235	260	270	300	3000	1100	1800	2650
5	GCD-350	NTA855-G3	290	320	315	350	3400	1100	1750	3393
6	GCD-400	QSX15-G6	360	400	360	400	3500	1460	1800	4440
7	GCD-450	QSX15-G7	-	-	405	450	3500	1460	1800	4440
8	GCD-500	QSX15-G9	400	440	450	500	3500	1460	1940	4600
9	GCD-550	QSK19-G2	475	525	500	550	3700	1320	1930	4672
10	GCD-600	VTA28-G5	500	560	545	600	4000	1580	2200	6454
11	GCD-750	QSK23-G2	590	650	680	750	4200	1580	2200	6350
12	GCD-800	QSK23-G3	650	720	725	800	4200	1580	2200	6420
13	GCD-900	QST30-G3	725	800	810	900	4400	2080	2200	7650
14	GCD-1000	QST30-G4	800	880	900	1000	4500	2080	2200	7800
15	GCD-1250	KTA50-G3	1000	1120	1130	1250	5200	2080	2200	11300
16	GCD-1500	QSK50-G4	1230	1360	1360	1500	5600	2080	2200	13500

prime power : Overload of 10% is permitted for one

hour in twelve hours operation.

standby power : no overload is permitted.

